


	MIN.	TYP.	MAX.	
Α	.019	.020	.021	
В	.019	.020	.021	
С	.004	.005	.006	

REVISIONS									
ZONE	REV	ECN#	DESCRIPTION	DATE	ENG. APPR.	QC. APPR.	PROD. APPR.		
	Α	3898	INITIAL RELEASE	8/31/2020					



## NOTES:

- 1. LOT TRACEABILITY REQUIRED WITH EACH MANUFACTURING LOT.
- 2. CERTIFICATE OF COMPLIANCE REQUIRED.
- 3. ALL PARTS SHALL BE LABELED WITH A UNIQUE LOT NUMBER WHICH SHALL BE IDENTIFIED ON ALL CONTAINERS HOLDING PARTS.
- 4. CLEANLINESS: THE PARTS SHALL HAVE NO FOREIGN MATERIAL ON THEIR INTERNAL OR EXTERNAL SURFACES AND SHALL BE CLEANED USING A REPEATABLE PROCESS.
- 5. BOTTOM METALLIZATION SHALL BE COMPATIBLE WITH AU/SI EUTECTIC ATTACH METHODS.
- 6. MUST BE CAPABLE OF BONDPULL IN ACCORDANCE WITH MIL-STD-883, METHOD 2011.
- 7. MUST BE CAPABLE OF DIE SHEAR IN ACCORDANCE WITH MIL-STD-750, METHOD 2017 AND PER MIL-STD-883-2019.
- 8. BAKE TEST: 10PCS. @300°C FOR 5 MIN. IN OVEN(AIR ENVIRONMENT).
- 9. VISUAL & MECHANICAL INSPECTION TO COMPLY WITH THIS DRAWING & MIL-STD-883, METHOD 2010.

